



0	1	2	3	4	5	6	⏏
CODE: HOFB45TC0320R							
TYPE: 1 HO 415-57-5V NA							
230V~ 50/60Hz Th.Prot. Ins.CL.F							
2,95A 335/565W 1300Rpm C=6,3μF 450VL							
2,95A 355/580W 1300Rpm C=8,0μF 450VL							
2,93A 385/610W 1300Rpm C=10μF 450VL							
2,95A 415/645W 1300Rpm C=12,5μF 450VL							
DATA							
BLUE	COMMON						
BROWN	MAX-5 VEL.						
GREY	4 VEL.						
VIOLET	3 VEL.						
ORANGE	2 VEL.						
RED	MIN-1 VEL.						
YELLOW							
GREEN	C						
YELLOW/GREEN							

CLASS "F" MOTOR - BALL BEARING MANUFACTURED (Motore classe "F" - Esecuzione a Cuscinetti)	
SHELL (Fascia)	OPEN (Aperta)
END SHIELD - CABLE SIDE (Coperchio lato cavi)	OPEN (Aperta)
END SHIELD - OPPOSITE CABLE SIDE (Coperchio lato opposto cavi)	OPEN (Aperta)
ASSEMBLY SPECIFICATION No. (Normativa per note di montaggio)	EL.UN.0009
MECHANICAL SPECIFICATION No. (Normativa per note di controllo meccanico)	EL.CM.0002
ELECTRICAL SPECIFICATION No. (Prescrizione per controllo elettrico)	M.2296/1

Rel.	Date	Description	Executor signature	Checked
MODIFICATIONS				

For dimension without tolerance see standard UNI EN 22768-mK	Treatment	A3	Release
Material			
	Drawn Baronio G. Date 18/09/2012 Check <i>[Signature]</i> Scale ---	SINGLE PHASE MOTOR MOTOR 1 HO 415-57-5V NA 230V 50/60Hz Th.Prot. CL.F	Weight gr. _____ Ref. No Rds 13/ 0020
HOFB45TC0320R			