



0	1	2	3	4	5	6	⏏
CODE: HOFB45TC0321R							
TYPE: 1 HO 555-69-5V NA							
230V~ 50/60Hz Th.Prot. Ins.CL.F							
3,85A 510/830W 1300Rpm C=15μF 450VL							
4,10A 555/905W 1300Rpm C=18μF 450VL							
DATA							
BLUE	COMMON						
BROWN	MAX-5 VEL.						
GREY	4 VEL.						
VIOLET	3 VEL.						
ORANGE	2 VEL.						
RED	MIN-1 VEL.						
YELLOW	C						
GREEN	C						
YELLOW/GREEN	C						

CLASS "F" MOTOR - BALL BEARING MANUFACTURED (Motore classe "F" - Esecuzione a Cuscinetti)	
SHELL (Fascia)	OPEN (Aperta)
END SHIELD - CABLE SIDE (Coperchio lato cavi)	OPEN (Aperta)
END SHIELD - OPPOSITE CABLE SIDE (Coperchio lato opposto cavi)	OPEN (Aperta)
ASSEMBLY SPECIFICATION No. (Normativa per note di montaggio)	EL.UN.0009
MECHANICAL SPECIFICATION No. (Normativa per note di controllo meccanico)	EL.CM.0002
ELECTRICAL SPECIFICATION No. (Prescrizione per controllo elettrico)	M.2297/1

For dimension without tolerance see standard UNI EN 22768-mK				Treatment	A3		
Material							
		Drawn Baronio G. Date 22/01/2013 Check <i>[Signature]</i> Scale ---	SINGLE PHASE MOTOR MOTORE 1 HO 555-69-5V NA 230V 50/60Hz Th.Prot. CL.F			Weight gr. Ref. No Rds 13/ 0020	Release -
HOFB45TC0321R		HOFB45TC0321R					
Rel. Date Description Executor signature Checked		MODIFICATIONS					
1		DRAWING MADE BY CAD HAND MADE MODIFICATIONS ARE FORBIDDEN					
2		THIS DRAWING IS OUR PROPERTY. ANY PARTIAL OR COMPLETE COPY IS FORBIDDEN WITHOUT PREVIOUS WRITTEN AUTHORISATION					